



**DT ALLIANZ LIFTS
PRIVATE LIMITED**

(Formerly Known as Alliance Elevators)


Technology in **Elevators**



Lift Servicing, Installation, Upgrades & Maintenance


Welcome to
the Future of
VERTICAL MOTION

Machine Room System (MR)




Geared Traction Machine

Machine Roomless System (MRL)



Gearless Machine

Hydraulic System (MRL)



Hydraulic Cylinder



Feature Rich Elevators

DT ALLIANZ LIFTS PVT. LTD. Passenger Elevators comes with many enviable features*




Door Frames :

DT Allianz Lifts come with elegant door frames in Stainless Steel or Mild Steel finishes that gives strength as well as enlarged appearance.



Infrared Door Detector :

A full height curtain of infrared beams to prevent accidental closing of the door.




Auto Shut off Car Light / Fan :

If there is no call for a specific period, the car lighting and ventilation Fan will automatically turn off to conserve energy.



Regenerative Converter :

For energy conservation, power generated by a traction machine can be used by other electrical systems in the building.




Over Load Indicator :

In case the lift is overloaded than its rated capacity an audible / visual signal turns on.



Supervisory Panel :

Each elevator status and operation can be remotely monitored and controlled through a panel installed in a building's supervisory room etc.



Automatic Rescue Device (ARD) :

Automatically takes the lift to the nearest level in case of power interruption, doors open to facilitate the safe evacuation of passengers.




VVF Controllers :

The Variable Voltage Variable Frequency (VVF) control ensures 50% energy savings. It also creates a super comfortable ride quality with jerk free starts and stops. Smooth acceleration and deceleration and no landing variations. In the long run, this prevents wear and tear of components which means less downtime and huge saving on spares.



Stainless Steel Buttons :

Sophisticated design buttons flush with backplate having Orange / Red illumination with engraved numbers. Highly temper resistance with / without braille markings.



VVVF Door Controller :

Silken smooth door movement. Advanced features like adjustable independent times for opening and closing. Slow nudging feature ideal for high traffic situations.



LCD / TFT Position Indicators :

The LCD or TFT display of Car operating panel shows the car position, travel direction and elevator status message.



Floor Annunciator :

Recorded voice with music announces the floor number on arrival.



Inter communication system :

A system which allows communication between passengers inside the car and the building personnel.



Extended Door Open Button :

When the button inside the car is pressed the doors will remain open longer to allow loading and unloading of baggage, a stretcher etc.



Fire Emergency Operation :

To enable fire service personnel to take over complete control over the elevator.



Car Arrival Chime :

Electronic chimes sound to indicate that Car has arrived floor (for duplex only)



Emergency Car Lighting :

Car Lighting which turns on immediately when power fails, providing a minimum level of lighting within the car.

Cabin Designs

Freedom of designs

Create the look and feel you like. Combine colors, materials, lighting, mirrors, handrails and fixtures to achieve the ambiance that fits both your ideas and your building.

Choose from one of our four interior design lines or design the whole car to your own taste.



DTA-01
Stainless Steel & Half Glass Designer Cabin



DTA-02
M.S. & Glass Designer Cabin



DTA-03
Wooden & Glass Designer Cabin




DTA-04
Stainless Steel & Glass Designer Cabin



DTA-05
Stainless Steel & Glass Decorative Cabin



DTA-06
S.S. Hairline & Glass Designer Cabin





**DT ALLIANZ LIFTS
PRIVATE LIMITED**
(Formerly Known as Alliance Elevators)

Design lines, colors and materials.
Design that speaks to your senses.



DTA-07
Rose Gold & Glass Designer Cabin



DTA-08
Golden Designer Cabin



DTA-09
Golden Designer Cabin




DTA-10
Golden Designer Cabin




DTA-11
S.S. Hairline & Designer Cabin



DTA-12
Golden Designer Cabin





The Stylish Way to
Brand Your Elevator

Automatic Door



Center Opening Auto Door (Small Vision)



Hairline Finish Telescopic
Autodoor



Center Opening
Plain S.S. Door



Rose Gold Center Opening
Autodoor



Center Opening Auto Door
(Four Panel)



Full Glass Door



Full Vision Glass Door




Half Glass Autodoor

Manual Door




Manual Imperforates Door



Manual Collapsible Door



Manual Telescopic Door



Manual Swing Door



M.S. Powder Coated Frame
Full Glass Swing Door

Capsule Elevator

Smooth Operation Comfortable Travel

Our premium capsule elevators fast and highly cost-effective way to create a full-glass elevator solution for your building.

There are multiple car models to choose from, as well as a wide range of interior design options and other customization possibilities.

| | |
|----------------------------|---------------------|
| Available Rated Speed : | 1.0, / 1.5 / 2 MPS |
| Max Travel Height : | 66 M |
| Available Rated Capacity : | 408 to 1088 Kgs |
| Max Passengers : | 06 to 16 Passengers |



Square Glass Cabin





Five Side Glass Cabin



S.S. Round Glass Cabin



Powder Coted Round
Glass Cabin




Type - A

| Load | | Car Inside | | | | Left Well | | | | Entrance |
|--------|------|------------|------|------|-----|-----------|------|------|------|----------|
| Person | Kgs. | A | B | J | G | C | D | F | H | E |
| 8 | 544 | 1000 | 1200 | 1250 | 600 | 2000 | 1225 | 1230 | 1000 | 800 |
| 10 | 680 | 1100 | 1300 | 1400 | 650 | 2200 | 1325 | 1330 | 1100 | 900 |
| 13 | 884 | 1200 | 1400 | 1550 | 700 | 2400 | 1425 | 1430 | 1100 | 1000 |
| 16 | 1068 | 1300 | 1500 | 1700 | 750 | 2800 | 1525 | 1530 | 1200 | 1200 |

Type - B

| Load | | Car Inside | | | Left Well | | | | Entrance |
|--------|------|------------|------|-----|-----------|------|------|-----|----------|
| Person | Kgs. | A | B | G | C | D | F | H | E |
| 6 | 408 | 1000 | 1100 | 200 | 1800 | 1250 | 1230 | 470 | 700 |
| 8 | 544 | 1150 | 1200 | 200 | 2000 | 1380 | 1350 | 520 | 800 |
| 10 | 680 | 1250 | 1300 | 250 | 2200 | 1450 | 1480 | 580 | 900 |
| 13 | 884 | 1400 | 1400 | 300 | 2400 | 1550 | 1630 | 650 | 1000 |
| 16 | 1068 | 1550 | 1500 | 350 | 2800 | 1780 | 1650 | 790 | 1200 |





Manual Door



Passenger Elevator

Manual Door

Manual door elevators are durable by design and accurate by technology. We have a wide range of these elevators which are most reliable and designed to suit every construction requirement and provide best vertical transportation solutions, with trouble free performance and low maintenance cost.

These elevators are a perfect blend of Cost friendly and robust performance elevator applications. They have an excellent record of customer satisfaction.



Safe




Robust




Lots of Options for
Interior and Fixtures

Available Rated Speed **0.63 / 1.0, / 1.5 / 2 MPS**
Max Travel Height **66 M**
Available Rated Capacity **272 to 1360 Kgs**
Max Passengers **04 to 20 Passengers**




COLLAPSIBLE DOOR LANDING



Hoistway Machine Room Plan For Manual Door

| Load | | Lift Well | | Car Inside | | Entrance | Machine Room | | |
|--------|--------|-----------|-------|------------|-------|----------|--------------|-------|--------|
| Person | Weight | Width | Depth | Width | Depth | | Width | Depth | Height |
| In Kg. | | A | B | C | D | E | F | G | H |
| 4 | 272 | 1600 | 1250 | 1100 | 700 | 700 | 3000 | 3000 | 2500 |
| 5 | 340 | 1600 | 1300 | 1100 | 850 | 750 | 3000 | 3200 | 2500 |
| 6 | 408 | 1670 | 1370 | 1100 | 1000 | 750 | 3000 | 3500 | 2500 |
| 8 | 544 | 1800 | 1600 | 1300 | 1100 | 750 | 3200 | 3500 | 2500 |
| 10 | 680 | 1850 | 1800 | 1350 | 1300 | 1000 | 3500 | 4000 | 2500 |
| 13 | 884 | 2500 | 1600 | 2000 | 1100 | 1000 | 4000 | 4200 | 2500 |
| 16 | 1088 | 2500 | 1800 | 2000 | 1300 | 1000 | 4500 | 4800 | 2500 |
| 20 | 1360 | 2500 | 2050 | 2000 | 1550 | 1000 | 5000 | 5000 | 2500 |

Hoistway Elevation Drawing






Passenger Elevator

Auto Door

Automatic doors at grocery stores and office buildings mainly exist for convenience. The automatic doors in an elevator, on the other hand, are absolutely essential – they keep people from falling down an open shaft.




Elevators use two different sets of doors: doors on the cars and doors opening into the elevator shaft. The doors on the cars are operated by an electric motor, which in turn is operated by the elevator computer.



Top grade door machine system

Fully computerized VVVF closed-loop control mode fulfills the smooth operation. It needs no position switch. Internal self-tuning function records various floor door widths by memory. It ensures the accurate and proper door-opening.

| | |
|--------------------------|---------------------------|
| Available Rated Speed | 0.63 / 1.0, / 1.5 / 2 MPS |
| Max Travel Height | 66 M |
| Available Rated Capacity | 272 to 1360 kgs. |
| Max Person | 04 to 20 Passengers |



| Load | | Car Inside | | | Lift Well | | Entrance | | Pit | Overhead |
|--------|------|------------|-------|--------|-----------|-------|----------|--------|-------|----------|
| Person | Kgs | Width | Depth | Height | Width | Depth | Width | Height | Depth | Height |
| 6 | 408 | 1100 | 1000 | 2150 | 1850 | 1400 | 700 | 2000 | 1600 | 4800 |
| 8 | 544 | 1100 | 1300 | 2300 | 1950 | 1700 | 800 | 2000 | 1600 | 4800 |
| 10 | 680 | 1300 | 1350 | 2300 | 2050 | 1750 | 800 | 2000 | 1600 | 4800 |
| 13 | 884 | 1300 | 1700 | 2300 | 2100 | 2100 | 900 | 2000 | 1600 | 4800 |
| 16 | 1088 | 1500 | 1750 | 2300 | 2350 | 2150 | 1000 | 2000 | 1600 | 4800 |
| 20 | 1360 | 1500 | 2000 | 2300 | 2350 | 2400 | 1000 | 2000 | 1600 | 4800 |

Above dimension are default / indicative



Hospital Elevator

Can Save Time for Quick Rescue

- The Hospital Elevator is designed Especially for Patient Vertical Transportation in Hospital.
- In Elevator Cabin Wheelchair & Stretcher Can be Accommodated.
- No Jerk is experienced at the Starting & Stopping of Elevator.
- Size of Elevator Cabin & Doors can be Adjustable as Availability of Hoistway.
- Elevator Car with two Opposite Side Opening is Possible, if required.
- Cabin is washable with Wet Cloth.



Intellectual Control



Noise Reducing




Smooth and Comfortable

Available Rated Speed **0.63 / 1 MPS**
 Max Travel Height **66 M**
 Available Rated Capacity **544 to 1768 Kgs**
 Max Passengers **08 to 26 Passengers**




Safety Door Edge (SDE)

A mechanical safety device with a micro-switch reverses closing doors if there is physical contact with a passenger or an object.



Hoistway Elevation Drawing



Automatic Centre Opening Door

| Capacity | | Shaft W | Shaft D | Car W | Car D | Shaft W | Shaft D | Car W | Car D | Entrance |
|----------|------|---------|---------|-------|-------|---------|---------|-------|-------|----------|
| Person | KG. | A | B | C | D | A | B | C | D | E |
| 10 | 680 | 1900 | 3000 | 1000 | 2400 | 1700 | 3000 | 1000 | 2400 | 700 |
| 15 | 1020 | 1900 | 3000 | 1000 | 2400 | 1700 | 3000 | 1000 | 2400 | 800 |
| 20 | 1360 | 2300 | 3000 | 1300 | 2400 | 1950 | 3000 | 1300 | 2400 | 900 |
| 26 | 1768 | 2600 | 3000 | 1600 | 2400 | 2100 | 3000 | 1600 | 2400 | 1000 |

Collapsible Door Can Be Provided If Required.

Automatic Telescopic Door



**DT ALLIANZ LIFTS
PRIVATE LIMITED**

(Formerly Known as Alliance Elevators)

Goods Elevator



Goods Elevator

Save Valuable Time as
Well As Energy

Special Features:

- Goods Lifts are amalgamation of Cranes and lift technology.
- Mechanisms Mounted on Fabricated Frame
- All Door entries fitted with collapsible doors.
- Cabin height not less than 2100mm.
- Cabin floors are covered with chequer plate.
- If one rope fails another rope holds the cabin from falling.
- If any gate is opened Goods Lift Will not operate.
- All floor doors are fitted With limit switches.

Available Rated Speed **0.50 / 1.00 / 1.50 MPS**
Max Travel Height **66 M**
Available Rated Capacity **500 to 3000 Kgs**



Aluminum Checker Plate





M.S. Checker Plate



Heavy Duty Traction Machine



Accurate Leveling



| Load | Lift Well | | Car Inside | | Entrance | | Machine Room | | UPTO 0.7 M / SEC. | |
|--------|-----------|------|------------|-------|----------|-------|--------------|--------|-------------------|------|
| Weight | Width | | Depth | Width | Depth | Width | Depth | Height | Pit | O.H. |
| IN KG | A | B | C | D | E | F | G | H | K | M |
| 500 | 1900 | 1500 | 1100 | 1200 | 750 | 3000 | 3800 | 2500 | 1600 | 4800 |
| 1000 | 2300 | 2100 | 1400 | 1800 | 1000 | 3000 | 4000 | 2500 | 1600 | 4800 |
| 1500 | 2600 | 2300 | 1700 | 2000 | 1250 | 3200 | 4200 | 2500 | 1600 | 4800 |
| 2000 | 2600 | 2800 | 1700 | 2500 | 1500 | 3200 | 4200 | 2500 | 1600 | 4800 |
| 2500 | 2900 | 2800 | 2000 | 2500 | 1500 | 3500 | 4400 | 2500 | 1600 | 4800 |
| 3000 | 2900 | 3300 | 2000 | 3000 | 2000 | 3500 | 4500 | 2500 | 1600 | 4800 |
| 4000 | 3400 | 3300 | 2500 | 3000 | 2000 | 4000 | 4600 | 2500 | 1600 | 4800 |
| 5000 | 3400 | 3900 | 2500 | 3600 | 2500 | 4500 | 4500 | 2500 | 1600 | 4800 |

All Dimension are in mm. This is General Data, without notice.



MRL Elevator



Reduction in Elevator Equipment Area of **35%**


MRL Elevator

Machine Roomless Elevator



Less Space Less Energy More Flexibility

Brings you a revolutionary concept in the field of elevators to give you absolute freedom in designing-MRL-Machine Room Less Elevators. Our exclusive Machine room less elevators brings aesthetic enhancements for your structure.

| | |
|--------------------------|---------------------|
| Available Rated Speed | 1.00 / 1.50 / 2 MPS |
| Max Travel Height | 66 M |
| Available Rated Capacity | 340 to 1768 Kgs |
| Max Passengers | 05 to 26 Person |



New generation permanent magnet synchronous gearless traction machine



Construction Parameters

| Capacity | | Car Inside | | | Lift Well | | Clear Entrance | Clear Opening At Landing |
|----------|-----|------------|------|------|-----------|-----|----------------|--------------------------|
| Person | KGS | A | B | C | D | E | F Auto Door | F Manual Telescopic |
| 6 | 408 | 1200 | 900 | 1800 | 1400 | 700 | 780 / 2100 | 1450 / 2350 |
| 8 | 544 | 1300 | 1100 | 1900 | 1600 | 800 | 880 / 2100 | 1600 / 2350 |
| 10 | 680 | 1300 | 1300 | 1900 | 1800 | 800 | 880 / 2100 | 1600 / 2350 |
| 13 | 884 | 1600 | 1400 | 2200 | 1900 | 900 | 980 / 2100 | 1700 / 2350 |

- Above dimension may vary as per different types of and equipments.
- All dimensions are in mm.



100% Eco Friendly



**DT ALLIANZ LIFTS
PRIVATE LIMITED**

(Formerly Known as Alliance Elevators)

Home Elevator



Home Elevator

Luxury and Convenience in Your Home

Home Elevator is designed to meet vertical transportation needs in private bungalows. It is the ideal solution for elderly and impaired persons who can finally move autonomously and free from stairs.

It is a modern product, designed and manufactured to meet a wide range of needs from the garage to the roof, you can move effortlessly up to 4 floors.

| | |
|--------------------------|-------------------|
| Available Rated Speed | 0.30 / 0.63 MPS |
| Max Travel Height | 12 M |
| Available Rated Capacity | 300 to 450 Kgs |
| Max Passengers | 4 to 6 Passengers |

Main feature and benefits :

- Runs with single phase power supply.
- Required very compact overhead space and pit area.
- Saves up 40% energy compared to hydraulic elevator.
- Noiseless and vibration free.
- Easy to install and maintain.

Mini Gearless Machine




Save Energy




Low Noise



Comfortable




HOISTWAY ELEVATION PLAN



| Door Operation | Load | | Lift Well | | Car Inside | | Entrance | Speed | Pit | Over Head |
|----------------|---------|-----|-----------|------|------------|------|----------|-------|-----|-----------|
| | Persons | KGS | C | D | A | B | E | (MPS) | | |
| Manual Door | 3 | 204 | 1100 | 1200 | 810 | 700 | 700 | 0.3 | 550 | 3100 |
| Manual Door | 4 | 272 | 1300 | 1400 | 800 | 1200 | 700 | 0.3 | 550 | 3100 |
| Auto Door | 3 | 204 | 1250 | 1250 | 810 | 700 | 700 | 0.3 | 550 | 3100 |
| Auto Door | 4 | 272 | 1300 | 1600 | 850 | 1150 | 700 | 0.3 | 550 | 3100 |

Note : This Is Our Standard Data, If other Special Requirement Please Contact us.



Car Elevator

The Most Reliable Parking Assistants

Car elevators help to alleviate the problems of finding sufficient parking space in busy areas, and save on costly land in commercial space.

These lifts smoothly transport vehicles to the tops of building, or to basements and showrooms.



They are carefully engineered for independent access of vehicles in private homes or multi-family residences where space is valuable.

Available Rated Speed 0.30 / 0.50 MPS
Max Travel Height 30 M
Available Rated Capacity 2500 to 4000 Kgs




Bi-Partial Door

| Description | Vertical Transportation for Cars/ LMVs |
|------------------|--|
| Segment | Industrial applications & Car Parks |
| Max. travel (m) | 100 (Solutions available for higher travel) |
| Max. load (kg) | 500 - 5000 Kg (Solutions available for higher capacities) |
| Max. speed (m/s) | 0.5 mps (Solutions available for other speeds) |



Different Type Car Parking Lift



Two Car Parking System



Car Puzzle Parking



Electric Scissor Car Lift



**DT ALLIANZ LIFTS
PRIVATE LIMITED**
(Formerly Known as Alliance Elevators)

Hydraulic Elevator



Hydraulic Elevator

For Low Rise


Looking for a low-maintenance elevator Hydraulic elevator provide the advantages of being relatively inexpensive, safe and easy to maintain. They're very convenient and cost-effective solution for low-rise buildings with low traffic.

Hydraulic elevators have been rated the safest option for home elevators. They boast superb user friendliness and easy access machine room located at the basement. Once they are put in place, hydraulic elevators provide the smoothest rides possible.

| | |
|--------------------------|-------------------|
| Available Rated Speed | 0.30 MPS |
| Max Travel Height | 30 M |
| Available Rated Capacity | 204 to 408 Kgs |
| Max Passengers | 3 to 6 Passengers |



HOLE TYPE ACTING




It is a directly acting suspension with a simple or split piston.
It is the simplest solution of suspension for any load.

| Persons | Capacity Kg | Car-W (A) | Car-D (B) | Shaft-W (C) | Shaft-D (D) |
|---------|----------------|--------------|--------------|----------------|----------------|
| 3 | 225 | 800 | 1100 | 1500 | 1500 |
| 4 | 300 | 850 | 1050 | 1550 | 1550 |
| 5 | 375 | 1000 | 1200 | 1600 | 1600 |
| 6 | 450 | 1100 | 1250 | 1700 | 1700 |
| 8 | 600 | 1200 | 1500 | 1700 | 1800 |
| 10 | 750 | 1200 | 1700 | 1700 | 2000 |
| 12 | 900 | 1300 | 1800 | 1900 | 2100 |
| 15 | 1125 | 1300 | 2200 | 2000 | 2500 |
| 20 | 1500 | 1400 | 2500 | 2100 | 2800 |
| 24 | 1800 | 1500 | 2500 | 2200 | 2800 |



Service Goods Lift



COP & LOP

Car Operating Panel & Landing Operating Panel



EL 03 COP - LOP



SM : GRAND COP-LOP



A wide variety of operating panels for lifts with great flexibility in special construction.



ET-02C



ET-02L



SM : I TOUCH White COP-LOP



Vertical Display Effect



Horizontal Display Effect



TFT Color Display



Monochrome

Push Button



SM : Classic COP-LOP



SM : I TOUCH Black COP-LOP





**DT ALLIANZ LIFTS
PRIVATE LIMITED**
(Formerly Known as Alliance Elevators)

Green Installment Saving Environment Friendly




Save Energy



Low Noise



Comfortable



Gearless Traction Machine



MGI-127L
Gearless Machine



MRL Gearless Machine




Mini Gearless Machine

Lift Duty Reduction Geared Machine Units



Montanari Heavy Duty
Traction Geared Machine



M67
Geared Traction Machine




CAULDRON - 135N
Geared Traction Machine

Controller


The safe and More Energy-Saving Integrated control




Traction MR Geared Controller



STEP
Elevator Parallel
Integrated Controller



HEDEFSAN
CONTROLLER with ARD



STEP
Elevator Serial
Integrated Controller





Escalator

S310-35K COMMERCIAL ESCALATOR

- ▶ Escalator suitable for hotels, office buildings, super markets, and airports.
- ▶ The step width can be 600mm, 800mm and 1000mm.
- ▶ The inclination can be 30° & 35°.
- ▶ The alternative function includes VVVF, auto-lubrication & error analysis.
- ▶ The requirements can be customized.

Functions

- ▶ Automatic inspection status transformation
- ▶ Handrail entrance device
- ▶ Up and down start key
- ▶ Emergency button/operation brake control
- ▶ Broken step chain safety device
- ▶ Comb safety device/ Protection from over speed
- ▶ Non-reversing safety device
- ▶ Inspection device
- ▶ Overload protection
- ▶ Control device for handrail breakage
- ▶ Phase monitoring relay
- ▶ Auxiliary brake [H>6.0m]



Superb performance comes from stringent design



Smooth Operation




Long Service Life



Quiet Running - Quiet Drive Units

| | S310-35K60 | S310-35K80 | S310-35K100 |
|---|------------|------------|-------------|
| A | 600 | 800 | 1000 |
| B | 838 | 1038 | 1238 |
| C | 1200 | 1400 | 1600 |
| D | 1260 | 1460 | 1660 |
| E | 1838 | 2038 | 2238 |
| F | 18500 | 16900 | 15700 |




Safety is everything.

When passengers ride our elevators
we want them safe.



**DT ALLIANZ LIFTS
PRIVATE LIMITED**

(Formerly Known as Alliance Elevators)



New Installation

Installation works are carried out after discussions on the type of lifts required to meet the demands of the buildings, using the latest technology and equipment.

Maintenance Contract

We are one of the reliable and well know service providers for elevators maintenance. We offer our clients' annual maintenance contract for all types of lifts.

Modification

We modify our clients elevator with the latest and updated techniques, technology, design and compact features to ensure maximum safety and to reduce the energy cost.

Repair & Service

We possess dynamic professionals to provide repairing and other maintenance service at market price for better functioning of the elevators and its inner devices.



We are Technically Associated with



DT ALLIANZ LIFTS PRIVATE LIMITED

(Formerly Known as Alliance Elevators)

Plot No. 121, Yogipuram, Haridwar,
Uttarakhand - 249408.

Contact no. : +91 - 80575 41922
+91 - 91493 42673
+91 - 01334 - 650150.

Email : dayaltewari@dtallianzlifft.com
dt@dtallianzlifts.com

Website : www.dtallianzliftsindia.com

Branch Office :-

Uttarakhand :

- Aiiims Rishikesh, Uttarakhand - 249203.
- Near Om Complex, Haldwani, Uttarakhand - 263139.
- Shimla By Pass Road, Premnagar, Dehradun, Uttarakhand - 248007.

Himachal Pradesh :

- Near Tirupati Medicare, Paonta Carib, Himachal Pradesh - 173025.